

BO-G300

Grooved End Butterfly Valve

Indoor and Outdoor Use

UL, ULC Listed and FM Approved



Specifications

Size : 2 1/2" Through 8"
 Working Pressure : 300 PSI (21.5 Bars)
 Max. Test Pressure : 600 PSI (43.0 Bars)
 Working Temperature : 250°F (120°C)
 Factory Installed UL Approved Tampered Switch for Indoor and Outdoor Use

Materials

Body : Ductile Iron, Nylon-11 coated
 Disc : Al-Bronze, Ductile Iron, EPDM Encapsulated
 Stem : Stainless Steel, Hardened & Tempered
 Housing : Ductile Iron (ASTM A-536)
 Hand Wheel : Ductile Iron (ASTM A-536)

Dimensions

(Unit: mm/inch)

SIZE	A	B	C	D	E	F	G
2 1/2"	105(4.13)	96.4(3.80)	168(6.61)	73.1(2.88)	137(5.39)	125(4.92)	
3"	112(4.41)	96.4(3.80)	168(6.61)	88.9(3.50)	144(5.67)	125(4.92)	
4"	145(5.71)	115.4(4.54)	168(6.61)	114.3(4.50)	177(6.97)	125(4.92)	
6"	179(7.05)	132.4(5.21)	208(8.19)	168.3(6.63)	211(8.31)	225(8.86)	6.8(0.27)
8"	204(8.03)	147.4(5.80)	208(8.19)	219.1(8.62)	236(9.29)	225(8.86)	24.2(0.95)

