

FEATURES

PRO SEAL PLUS

TEMPERATURE RANGE USE:

Gases:

-15°F (-26°C) to 400°F (204°C)

Liquids:

-15°F (-26°C) to 400°F (204°C)

Brushable to -15°F (-26°C)

PROSEAL PLUS is specially formulated for the fire protection industry for use on all metal threaded connections, **FlowGuard Gold**®, **Blazemaster**®, and **Corzan**® pipe and fittings.

PRESSURE RANGE USE:

Gases:

Up to 5,000 PSI (351.5 kg/cm²)

Liquids:

Up to 10,000 PSI (703.1 kg/cm²)

U.S. FEDERAL SPECIFICATIONS:

Power Seal exceeds TT-S-1732

AVAILABLE SIZES:

Stock#	Size
506250PBT	250 ml
506500PBT	500 ml
Flat Top Can	
506000P	1L
Pail	
506005P	20 L



- **Non-Separating**
- **Grit Free Paste**
- **Non-Hardening**
- **Non-Toxic**
- **Easy Cleanup**
- **Indefinite Shelf Life**
- **Adheres to Oily Threads**

"FBC™ System Compatible indicates that this product has been submitted by the manufacturer for testing, and is monitored on an ongoing basis to assure its chemical compatibility with FlowGuard Gold®, BlazeMaster® and Corzan® pipe and fittings." The manufacturer also agrees not to change the product after passing the test. "FBC™, FlowGuard Gold®, BlazeMaster® and Corzan® are licensed trademarks of The Lubrizol Corporation."

Suitable for use on systems carrying:

Air; Glycerine; Glycol; Steam; Water (hot or cold)